Tapettitehdas
Pihlgren ja Ritola Oy

Traditional wallpaper

PR-001-27052021

Product description:	Decorative, surface-printed wallpaper.
Suitability:	Suitable for most dry indoor wall surfaces, including hardboard and chipboard, plaster, plasterboard and timber. Not suitable for bathrooms or damp environments.
Adhesive:	Starch or cellulose-based adhesive.
Installation temperature:	+18 – 25C^{o}
Roll length:	10,05m or 11,2m
Roll width:	48–54 cm
Wallpaper weight:	120–130 g/m^{2}
Repeat and match:	Straight, half-drop, or no match.
General attributes:	Wallpaper is printed on paper with a traditional surface-printing technique. All printing colours are water-soluble and solvent-free distemper paints. They consist of cellulose starch, water, chalk, pigments and tinting pastes. The wallpaper is finished with a light fixative agent, that doesn't form a solid film or coating.
Batch number:	The batch number is marked on the roll tag. Slight variations between different batches are possible; please ensure that all batch numbers are the same.
Washability:	The wallpaper is not washable. It can be cleaned only with a soft, dry cloth. Do not use any water or detergents.
Removability:	If the wallpaper should be removed, it can be done by applying water or diluted wallpaper paste on top of the paper. In a few minutes, the wallpaper can be peeled off.
Environment & Health:	This product has been independently tested to have very low emissions, and its use promotes good indoor air quality (Finnish M1 classification). Wallpaper waste can be recycled into other materials or utilized as energy, according to your local recycling legislation.

Tapettitehdas
Pihlgren ja Ritola Oy

Hanging instructions

Mix the wallpaper paste according to the manufacturer's instructions. We recommend using a powder that is starch- or cellulose-based, and does not contain any added glue or plastic. Prepare the walls properly to create a smooth, even surface. Measure the height of the wall and cut the required length, adding an extra 10–15 cm, using a sharp knife. Apply the paste evenly to the back of the wallpaper using a paste brush. Pay special attention to the edges, applying the paste thinly and evenly. Make sure the paste does not end up on the patterned side of the wallpaper. Fold the wallpaper strip inwards towards the centre and leave it to soak for about a minute. Then, gently lift it onto the wall, opening the top fold as you do so. Gently brush the strip onto the wall using a soft wallpaper brush. Never use plastic or metallic wallpapering tools. Open the bottom fold and brush the entire strip into place. Cut and paste the next strip, ensuring that the pattern is properly aligned. Wallpaper strips should be installed with a butt joint or a 1–2 mm overlap if preferred. Handle wet wallpaper with care, as it can easily become damaged. If paste does end up on the patterned side, dab it off quickly with a clean, dry cloth.

IMPORTANT: Do not use water or a wet sponge to clean off excess paste.

Trim off any excess with a sharp knife once the paste is almost dry. Leave the wallpapered walls to dry undisturbed for at least a 24 hours. You can clean your finished wall lightly with a soft, dry fabric when necesarry. Do not use water or detergents.
See further hanging instructions: www.tapettitehdas.fi/en/instructions/.

Please note

Pihlgren & Ritola wallpapers are manufactured using a traditional printing technique, high-quality unbleached paper and water-based distemper paints. Every batch is unique and has its own, beautifully handmade appearance. Our wallpapers are products of traditional craftsmanship, therefore minor variations in the pattern can be expected. There may also be variations between different wallpaper print runs; for this reason, all rolls installed in the same room should be from the same production batch. The batch number can be found on the roll label. Should you have any concerns about the quality of the wallpaper, please contact our customer service or your local retailer before installation.

TEHTY SUOMESSA
MADE IN FINLAND

RAKENNUSMATERIAALIN PÄÄSTÖLUOKKA · RTS · M1

Tapettitehdas
Pihlgren ja Ritola Oy

CE
21
Pihlgren ja Ritola Oy, PL 43, FI-37801 Akaa, Finland +358 3542 1090
PR-001-27052021
EN 15102:2019
Internal finishes of walls
Rection to fire: D-s3,d2 Release and emission of formaldehyde: compliant Migration of heavy metals and specific elements: compliant Release of vinyl chloride monomer: compliant Content of specific dangerous substances: compliant Emission of other dangerous substances into indoor air: compliant Sound absorption: NPD Thermal resistance: NPD
https://www.tapettitehdas.fi/en/instructions

This product specification is issued according to the best possible knowledge available to Pihlgren ja Ritola Oy. Information is based on laboratory tests, measurements, and first-hand experience. We cannot control the conditions in which the wallpaper is used, and therefore can only be held responsible of our own product, that fulfils all the quality standards available for traditional wallpaper. Our company does not bear any responsibility if the product is used against the Hanging Instructions or used against its original purpose. This product specification is up-to-date, and it replaces all previous specifications.